

THIS PAGE BLANK (USPTO)



The
Patent
Office



INVESTOR IN PEOPLE



The Patent Office
Cardiff Road
Newport
Gwent
NP9 1RH

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words public limited company may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

AmBrewster

Dated

20 April 1999

THIS PAGE BLANK (USPTO)

Patents Form 1/77

Patents Act 1977
(Rule 16)

The
Patent
Office

THE PATENT OFFICE

G

21 APR 1998

RECEIVED BY POST

21APR98 E354367-1 D01529
P01/7700 25.00 - 9808293.6

Request for grant of a patent

(See the notes on the back of this form. You can also get
an explanatory leaflet from the Patent Office to help
you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

D7184 GB

9808293.6

2. Patent application number

(The Patent Office will fill in this part)

3. Full name, address and postcode of the or of
each applicant (underline all surnames)

AGCO GmbH & Co
Johann-Georg-Fendt Strasse 4
D-87616 Marktoberdorf
GERMANY

Patents ADP number (if you know it)

0739211/001

If the applicant is a corporate body, give the
country/state of its incorporation

GERMANY

4. Title of the invention

VEHICLE COOLING RADIATOR ARRANGEMENT

5. Name of your agent (if you have one)

Paul Simpson

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)

AGCO Limited
PO BOX 62
Banner Lane
Coventry
CV4 9GF

Patents ADP number (if you know it)

0739211/001

6. If you are declaring priority from one or more
earlier patent applications, give the country
and the date of filing of the or of each of these
earlier applications and (if you know it) the or
each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise
derived from an earlier UK application,
give the number and the filing date of
the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right
to grant of a patent required in support of
this request? (Answer 'Yes' if:

Yes

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an
applicant, or

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document


Continuation sheets of this form	0
Description	4
Claim(s)	2
Abstract	1
Drawing(s)	2+2

10. If you are also filing any of the following, state how many against each item.

Priority documents	0
Translations of priority documents	0
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	0
Request for preliminary examination and search (Patents Form 9/77)	1
Request for substantive examination (Patents Form 10/77)	0
Any other documents (please specify)	Fee Sheet

11. I/We request the grant of a patent on the basis of this application.

Signature



Date 10-4-98

12. Name and daytime telephone number of person to contact in the United Kingdom
- Paul Simpson - 01203 851254

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

VEHICLE COOLING RADIATOR ARRANGEMENT

The invention relates to an arrangement of three or more cooling radiators for a utility vehicle, such as an agricultural tractor.

Powerful utility vehicles, such as agricultural tractors, for example, require a number of radiators in order to re-cool the working media, such as coolant water for the engine transmission oil and hydraulic oil amongst others, as they become heated during use. These days, it is common practice to provide the requisite radiators in a parallel arrangement one after the other so that the coolant air flows through radiators. However, there are certain disadvantages to this layout. Arranging the radiators one after the other results in a high resistance to air flow which, apart from making it necessary to provide a disproportionately powerful fan, can also cause lead to an interruption in the flow, which results in the radiators becoming overheated. The lower temperature differential available to the radiators also makes it necessary to provide radiators of a larger size. In addition, any dirt which gets into radiator fins, particularly those of the radiators at the rear, is very difficult or totally impossible to remove completely without dismantling the radiators. The presence of dirt poses the risk of local overheating in the radiators.

An objective of the invention is to provide an arrangement of three or more radiators of the generic type outlined above which is efficient, easy to maintain and not susceptible to failure.

According to the invention, an arrangement of cooling radiators is provided as set out in Claim 1 hereto.

THIS PAGE BLANK (USPTO)

The advantage of this arrangement is that the flow resistance is reduced when compared to three parallel radiators one after the other, which means that smaller radiators can be used to achieve the same cooling effect. Access to the radiators is also easier.

Preferably, the arrangement also has the features set out in Claim 2. In this arrangement, it is ensured that there are no "short circuits" of air flow resulting in localised hot spots on any of the radiators. Preferably access is provided means of the features set out in Claim 3.

Other preferable features are set out in the dependent Claims.

In general, the arrangement specifically described herein provides an inner chamber surrounded on most sides by radiators, which makes for ready access to the sides of the radiators on the interior, provided one of the radiators is pivotably mounted or detachable. Any dirt which has become stuck to the radiator fins can be removed easily using compressed air for example.

In addition, the radiator arrangement reduces the overall flow resistance in the radiators, resulting in low flow losses, thus providing a system of radiators which operates satisfactorily, even with a conventional fan, and is not susceptible to failure. This can largely be ascribed to the fact that relatively large cooling surfaces can be provided by arranging the radiators in the layout proposed by the invention, allowing the air to flow at a low rate and the fact that the entire coolant air induced, which does not contain any outside air, has to flow through two radiators only. Not to be overlooked, however, is the fact that a part of the dirt which might be contained in the air flowing through the radiators at the front is left in the inner chamber, which not only means that the efficiency of the rear radiator remains unaffected for a longer time but also the under-pressure prevailing in the inner chamber during this time is that required to induce a sufficient quantity of coolant air through the radiators connected at the front end.

In one practical arrangement of the invention, the radiators are mounted on a common radiator support. With this design, the radiator system can be assembled beforehand. This means that the entire radiator system can be provided as a unit which is pre-assembled by the radiator

THIS PAGE BLANK (USPTO)

manufacturer and fitted as part of the assembly process by the vehicle manufacturer. Advantageous features of the radiator support are set out in some of the following dependent claims.

In the case of cooling systems in which not all the possible locations for radiators will be used, for example because the vehicle does not have a hydraulic system and does not therefore require the radiator for the hydraulic oil, a practical solution is to replace the radiators arranged to front of the bracket with air permeable plates, whose resistance to the passage of air corresponds to that of the radiators which they have replaced. The under-pressure generated in the inner chamber due to the fan will then remain the same as it would be in a cooling system with a radiator for hydraulic oil and hence also the through-put of air through the system.

An embodiment of the invention will now be described in more detail below with reference to drawings. Of these:

Figure 1 is a perspective view of a cooling system seen from the front;

Figure 2 is a side view of the cooling system of Figure 1; and

Figure 3 is an exploded diagram of the cooling system of Figure 1.

The cooling system illustrated in the drawings is designed to be provided as a pre-assembled unit which can be mounted and secured directly onto a vehicle frame, not illustrated, in front of a fan.

This unit has a radiator support 1, on which several radiators are arranged. These are a rear water radiator designated by reference 2, a gear oil radiator 3, a booster air radiator 4, a combined radiator 5 for hydraulic oil and fuel as well as a condenser 6 for the air-conditioning system. Depending on the vehicle and the application for which it will be used, radiators which are not required can be replaced by radiators for other media or by air permeable plates. This being the case, the replacement plates can be designed in such a way that they have the same resistance to through-flow as the radiator which they replace.

THIS PAGE BLANK (USPTO)

Being the radiator with the largest surface area in this embodiment, the water radiator 2 is mounted in the interior of a bracket 1b, which is secured at the rear end region of the radiator support 1 so as to stand upright on the lower part 1a thereof. A fan deflector guide 1c is fixed to the bracket 1b behind the water radiator 2. All the other radiators are arranged in front of the bracket 1b in the longitudinal direction of the vehicle. Arranged the farthest forward, parallel with and at a long distance from the water radiator 2 is the condenser 6. The region between the water radiator 2 and the condenser 6 is delimited on the one side by the radiator 3, on the other side by the radiator 5 and at the top by the radiator 4, thereby forming an inner chamber 7. At their bracket-ends, the radiators 3 to 5 are secured to the bracket 1b at the peripheral regions and are joined to one another at their adjacent peripheral regions. The radiators 3, 5 at the sides are provided with plug elements 3a, 5a on the underside thereof and are supported in matching counter elements on the lower portion 1a. In order to fix the plug connections, the radiators 3, 5 are braced at their front end region with the lower portion 1a by means of long, vertical retaining screws 8.

Various points at which the radiators 3 to 5 abut with one another and with the radiator support 1 are designed so as to be air-tight due to matching contours of the radiators and/or by the use of appropriate sealing materials, so that air can enter the radiators via the inner chamber 7 only. As can be seen, the radiators 3, 5 at the sides are provided with matching formed plates 3b, 5b for this purpose, which fill the region between these radiators and the radiator 4 extending down towards the front on a level with the condenser 6.

The condenser 6 is not joined to either of the adjacent radiators 3 to 5. Instead, it is secured onto a frame 9 which can be pivoted by means of lateral joints 10 about one of the retaining screws 8, in order to provide ready access to the inner chamber 7 for maintenance work. The other retaining screw 8 is used to secure the condenser 6 in the closed position in which it is sealed against outside air by means of known locking elements 11, 12.

Lastly, in a modification of this embodiment, two or more sides of the chamber 7 are provided by a single, angled or curved radiator.

THIS PAGE BLANK (USPTO)

CLAIMS

- 1 An arrangement of 3 or more cooling radiators in a utility vehicle such as an agricultural tractor characterised in that the radiators together define three or more sides of a chamber.
- 2 An arrangement of radiators as claimed in Claim 1 characterised in that the said chamber is bounded on all sides by radiators or other wall members.
- 3 An arrangement as claimed in Claim 1 or Claim 2 characterised in that at least one of the radiators or wall members is releasably mounted to provide access to the chamber.
- 4 An arrangement as claimed in Claim 3 characterised in that the said releasably mounted radiator or wall member is pivotally mounted with respect to the radiators or other radiators.
- 5 An arrangement as claimed in any preceding claim characterised in that the radiators and/or wall members are mounted on a common support.
- 6 An arrangement as claimed in Claim 5 characterised in that the support consists of a base part and a bracket upstanding from the region of one end of the base part.
- 7 An arrangement as claimed in Claim 6 characterised in that a water cooling radiator is mounted with an airtight seal in the said upstanding bracket.
- 8 An arrangement as claimed in Claim 3 or Claim 4 and in Claim 5, 6 or 7, characterised in that, with the exception of the said releasably or pivotally mounted radiator, all the said cooling radiators are sealingly joined to each other and/or to the common support to form a rigid unit.

THIS PAGE BLANK (USPTO)

- 9 An arrangement as claimed in Claim 6 or any claim dependent thereon characterised in that the cooling radiators defining two opposed sides of the chamber are retained on the base portion by means of a plug and socket connection together with retaining screws.
- 10 An arrangement as claimed in Claim 2 or any claim dependent thereon characterised in that some or all of any said wall members comprise air permeable plates, having a predetermined resistance to air flow therethrough.
- 11 An agricultural tractor including an arrangement of cooling radiators as claimed in any preceding claim.
- 12 An agricultural tractor as claimed in Claim 10 having an engine hood which slopes downwardly towards the front thereof and in which the said cooling arrangement is enclosed at the forward end thereof, the cooling radiator arrangement including front and rear substantially parallel planar radiators, the major faces thereof facing substantially in the direction of movement of the tractor, and the said rear radiator having a major face of greater area than that of the said front radiator.
- 13 A tractor as claimed in Claim 12 when dependent upon Claim 7 wherein the said rear radiator comprises the said cooling water radiator.
- 14 An arrangement of cooling radiators substantially as herein specifically described with reference to the accompanying drawings.

THIS PAGE BLANK (USPTO)

ABSTRACT

Vehicle Cooling Radiator Arrangement

An arrangement of radiators (2-6) for a utility vehicle, eg an agricultural tractor, comprising three or more cooling radiators which together define a chamber (7), optionally with some of the walls formed by perforated plates instead of radiator elements. One of the radiator elements may be pivotally mounted with respect to the others to provide access to the chamber. The arrangement of radiators may be mounted on a common support (1).

Figure 3

THIS PAGE BLANK (USPTO)
